

# Skeie | Drama™

TECHNICAL SPECIFICATION

skeie®

Skeie AS, P.O. Box 4,  
N-4301 Sandnes, Norway

T +47 51 97 45 00

F +47 51 97 45 01

E seating@skeie.com

www.skeie.com

Reg.No. NO981505409MVA

## DIMENSIONS

Low back, 935mm: C/C 550mm, 560mm

High back, 1095mm: C/C 550mm, 560mm

## FRAME CONSTRUCTION

ST-37 steel alloy.

Supporting steel structure: 60 x 40 x 3 mm.

Standard floor fixing: 240 x 156 x 8 mm steelbracket fixed to the rear of the tread.

Powder coated steel in standard RAL colors.

The chair is suitable for fixing in the riser, flat floor, and in straight or curved rows.

All fixings in chair are metal to metal and floor fixed for every other chair.

## SEAT

Seatpad in cold moulded polyurethane foam w/ integrated 19 x 2 mm steelframe, thickness 100 mm.

Smooth, quiet tip-up spring mechanism - N.T.I. approved according to ISO 7173, Level 5 (highest level).

Upholstery sewn to measurements and easily removable with zipper solution.

## SEATBACK

Woodback 935mm or 1085mm: 16mm plywood with upholstered seat double and cut foam.

## ARMREST

Standard: Figgjo armrest in molded laminated wood: thickness 20 mm, width 40 - 80 mm.

Alternative: Soma armrest in molded laminated wood: thickness 20 mm, width 40 - 80 mm.

Alternative: Curved steelframe of 40 x 8 mm flatiron w/ 12mm thick and 50mm wide beech or birch plywood veneer armrest.

Fully upholstered armrest sidepanel fixed to steelframe also available.

## OPTIONAL W/ WRITING TABLE

Foldable writing tablet in armrest, Notis A, 12 mm plywood w/ laminate top.

Top of armrest: 20 x 43 mm in beech or birch fixed to steeltube.

Armrest sidepanel is 6,5 mm plywood covered w/ fabric.

PS! Writing tablet in armrest increases the C/C with 10 mm.

## ADDITIONAL SPECIFICATIONS

Can be delivered according to EN 12727, Level 4.

Row and seatnumbers are available.

Other qualities and measurements are available upon request.

PS! C/C 500, 520, 580, 600 mm with tall back - please ask for Symposium 2052 configuration.