

Skeie | Rocker™

TECHNICAL SPECIFICATION

skeie®

Skeie Seating AS,
Svanholmen 19
N-4313 Sandnes, Norway

E: seating@skeie.com
www.skeie.com

Reg.No. NO913369947MVA

DIMENSIONS

| | |
|-----------------------------|------------------|
| Low back, 955mm: | C/C 550mm, 560mm |
| High back, 1040mm: | C/C 560mm |
| High back (extended width): | C/C 560mm |

FRAME CONSTRUCTION

ST-37 steel alloy.

Supporting steel structure: 60 x 40 x 3 mm.

Standard floor fixing: 240 x 156 x 8 mm steelbracket fixed to the rear of the tread.

Powder coated steel in standard RAL colors.

The chair is suitable for fixing in the riser, on flat floor and in straight or slightly curved rows.

All fixings in chair are metal to metal and floor fixed for every other chair.

SEAT

Seatpad in cold moulded polyurethane foam w/ integrated 19 x 2 mm steelframe, thickness 120 mm.

Smooth, quiet tip-up spring mechanism - N.T.I. approved according to ISO 7173, Level 5 (highest level).

Upholstery sewn to measurements and easily removable with zipper solution.

SEATBACK

Cold moulded polyurethane foam with integrated 19 x 2 mm steelframe, thickness 110 mm.

Upholstery sewn to measurements and easily removable with zipper solution.

ARMREST

Cupholder or table fixed to steelframe of armrest available.

Hana armrests in wood, width 70, 80 mm for C/C 550 mm.

Available with wood armrests and sidepanels for row-end chairs, and without sidepanels for middle seats.

ADDITIONAL SPECIFICATIONS

Can be delivered according to EN 12727, Level 4.

Row and seatnumbers are available.

Other qualities and measurements are available upon request.